# Trunk Mount Micom 3T

125-Watt HF-SSB Transceiver 1.6 - 30 MHz



The Micom 3T HF radio transceiver provides the highest level of reliability for long-range wireless communications of voice, fax, e-mail and data. The Micom 3T radio is primarily used as a mobile unit, with its trunk-mount configuration maximizing operation convenience while saving valuable cabin space.

With the most advanced technology and the latest features, the Micom 3T provides superb radio communication dependability and functionality and is priced to meet the needs of a wide range of organizations. An upgraded version of the Micom 2ET model—successfully used by thousands of organizations worldwide—the Micom 3T complies with the world's strictest standards for radio communication equipment, including MIL-STD-810, ALE per MIL-STD-188-141B and FED-STD-1045.



# Micom 3T

### 125-Watt HF-SSB Transceiver

## Establish a radio link fast & simple

- Automatic Link Establishment per MIL-STD-1045 & MIL-STD-188-141B standards
- ISB-ready (Independent Side Band)
- Full interoperability with other manufacturers' radios complying with the same ALE standards

#### Voice that is loud & clear

- Built-in voice quality system utilizes proprietary algorithms to filter out background noises, giving users exceptional communication clarity
- Selectable bandwidth allows fine tuning for optimal voice and data communications
- · Voice-activated digital squelch

#### User-friendliness

- New control head features a large LCD, full-dot matrix digital display and an enhanced keyboard for programming and setup. Radio operation can also be performed using a PC and a programming application as well as a USB keyboard.
- Multiple language display available
- Remote control allows the transceiver to be operated from a distance of up to 100 feet using the extended Control configuration

# Years of trouble-free, most advanced communications

- Upgrading to future technologies is easily done by installing new software into the transceiver's DSP unit
- Easily replaceable digital components ensure cost-effective maintenance
- Very high MTBF, as with all Micom radios
- Unique Built-In self Test system provides exceptional dependability

# Comprehensive communication & networking services

- Office-quality communication services integrating fax, e-mail and data transmission and reception
- **MultiNet** enabling integration of different HF radio networks into one seamless network, allowing excellent coordination between different operational nets.
- AMD (Automatic Message Display) for free and pre-set text messages
- **GPS** embedded application (optional)
- Multiport and additional front panel communication ports
- Secure voice and data

## A proven family of radio products

• The Micom 3T is member of the Micom transceiver family—fixed and mobile stations—covering the long-range wireless communication needs of thousands of organizations world-wide.

#### Major accessories

- · Automatic telephone interconnect
- · FM to HF repeater
- ATUs
- Antenna systems
- HF modems
- Secure voice and data
- AC Power Supply

## **Specifications**

Model: M91AMN0KV5-K Frequency range: 1.6–30 MHz

Number of channels: 200

Transmission: 125 Watt PEP average Reception: 100 KHz-30 MHz Rx

Operating voltage:  $13.8 \pm 20\%$ 

24 V operation (optional)

Audio bandwidth: 350 to 2700 Hz Data: 300 to 3300 Hz

Frequency stability: 0.6 PPM (0.1 PPM optional)

Frequency resolution: 10 H Operating temperature range:

-30°C to +60°C / -22°F to +140°F

Humidity: 95% @ 50°C / 122°F

Sensitivity (SINAD): SSB: 0.3  $\mu$  V for 10 dB SINAD

Dimensions: Control head

 Height:
 92 mm / 3.7 inch
 60 / 2.36

 Width:
 302 mm / 11.9 inch
 187 / 7.36

 Depth:
 285 mm / 11.3 inch
 70 / 2.75

 Weight:
 5.8 Kg / 12.8 lbs
 0.32 / 0.71

# Options:

- · PC control and programming software package
- USB for external keyboard
- micomLink interface
- ALE DTM/DBM
- Interface for secure voice device VP116

