



MOTOTRBO™ Remote Speaker Microphones Enhance Communication

Introducing Remote Speaker Microphones that offer IMPRES™, Windporting, Noise-Canceling Acoustics and/or IP57 Submersibility features



PMMN4025



PMMN4046

The MOTOTRBO portfolio has a wide variety of RSM solutions that meet the specific needs of radio users:

Education and Hospitality Professionals

These compact microphones have an audio jack for discreet communication needs and enhanced audio features such as windporting and/or IMPRES audio for school security, rallies, conventions and outdoor events

PMMN4024 – Remote Speaker Microphone with audio jack

PMMN4025 – IMPRES Remote Speaker Microphone with audio jack

PMMN4040 – Remote Speaker Microphone (IP57)

Manufacturing, Construction and Public Works Professionals

These durable RSMs have a larger speaker body making it ideal for users working at a job site or in the field. Windporting, IMPRES audio and/or IP57 submersibility help these users communicate even when Mother Nature is uncooperative.

PMMN4046 – IMPRES Remote Speaker Microphone with volume control (IP57)

PMMN4050 – IMPRES Remote Speaker Microphone with audio jack

Motorola's Remote Speaker Microphones (RSMs) are a vital two-way radio accessory solution for users who need to talk and listen without removing the radio from their belt or carry case. These RSMs boast new features that give users flexible solutions and the confidence of clear, understandable communication even in the most adverse conditions.

The MOTOTRBO portfolio has a wide range of RSMs that provide enhanced communications with advanced features such as the following:

- Motorola's state-of-the-art IMPRES technology allows communication between the radio and the audio accessory. The result is optimal audio performance and increased customization assuring the highest quality communication.
- The windporting feature dramatically lessens noise caused by high winds and other severe weather conditions.
- When a user speaks directly into the microphone, the noise-canceling acoustics utilize a directional microphone that is designed to eliminate the ambient noise.
- IP57 submersibility ratings provide reliable communications even in wet conditions.
- When injuries or emergencies strike, emergency-button equipped RSMs can be used to signal that the operator needs help.
- A volume switch allows the user to adjust the audio volume without having to access the radio.
- An audio jack located at the head of the microphone allows users to receive discreet audio communication, with an additional earpiece accessory.
- RSMs are available in both small and large housings. The small housing is compact and lightweight. The large housing is beneficial for users wearing gloves or in rugged conditions.

PRODUCT SPECIFICATIONS

	PMMN4046	PMMN4050	PMMN4024	PMMN4025	PMMN4040
MICROPHONE ACOUSTICS					
Microphone Type:	Omni-directional	Directional	Omni-directional	Omni-directional	Omni directional
Sensitivity:	-44dBV typical	-47dBV typical	-44dBV typical	-44dBV typical	-44dBV typical
SPEAKER ACOUSTICS					
Diameter:	45mm	45mm	45mm	45mm	45mm
Output power:	0.5W at rated audio	0.5W at rated audio	0.5W at rated audio	0.5W at rated audio	0.5W at rated audio
Output Level:	90dB SPL typical	90dB SPL typical	90dB SPL typical	90dB SPL typical	90dB SPL typical
Maximum Output Level:	≤ 120dB SPL at maximum volume	≤ 125dB SPL at maximum volume	≤ 120dB SPL at maximum volume	≤ 120dB SPL at maximum volume	≤ 120dB SPL at maximum volume
Frequency Response:	300Hz – 3200Hz	300Hz – 3200Hz	300Hz – 3200Hz	300Hz – 3200Hz	300Hz – 3200Hz
Distortion (THD):	<15% (RX)	<15% (RX)	<15% (RX)	<15% (RX)	<15% (RX)
AUDIO JACK					
Audio Jack Type:	None	3.5mm unthreaded jack	3.5mm unthreaded jack	3.5mm unthreaded jack	None
Compatible Earpieces:	N/A	AARLN4885, WADN4190, PMLN4620, RLN4941	AARLN4885, WADN4190, PMLN4620, RLN4941	AARLN4885, WADN4190, PMLN4620, RLN4941	N/A
Maximum Output Level:	N/A	≤ 118 dB SPL	≤ 118 dB SPL	≤ 118 dB SPL	N/A
BODY					
Dimensions (W x L x D):	60mm x 78mm x 28mm (without clip)	60mm x 78mm x 28mm (without clip)	55mm x 60mm x 27mm (without clip)	55mm x 60mm x 27mm (without clip)	55mm x 60mm x 27mm (without clip)
Weight:	220 grams	220 grams	194 grams	194 grams	194 grams
POWER					
Power Source:	Radio battery	Radio battery	Radio battery	Radio battery	Radio battery
CABLE					
Flex Life:	50,000 cycles	50,000 cycles	50,000 cycles	50,000 cycles	50,000 cycles
Pull Strength:	40lbs, minimum tensile, in-line	40lbs, minimum tensile, in-line	40lbs, minimum tensile, in-line	40lbs, minimum tensile, in-line	40lbs, minimum tensile, in-line
CONTROLS					
Emergency:	Orange button	None	None	Orange button	None
Volume:	Toggle switch	None	None	None	None
Side Button:	Programmable Option	None	None	None	None
ENVIRONMENTAL SPECIFICATIONS					
Operating Temp:	-30 C to +60 C	-30 C to +60 C	-30 C to +60 C	-30 C to +60 C	-30 C to +60 C
Storage Temp:	-55 C to +85 C	-55 C to +85 C	-55 C to +85 C	-55 C to +85 C	-55 C to +85 C
Humidity:	90-95% relative humidity at +50 C for 8 hours	90-95% relative humidity at +50 C for 8 hours	90-95% relative humidity at +50 C for 8 hours	90-95% relative humidity at +50 C for 8 hours	90-95% relative humidity at +50 C for 8 hours
Rain:	MIL810F Method 506.4	MIL810F Method 506.4	MIL810F Method 506.4	MIL810F Method 506.4	MIL810F Method 506.4
Salt/Fog:	MIL810F Method 509.4, Procedure 1	MIL810F Method 509.4, Procedure 1	MIL810F Method 509.4, Procedure 1	MIL810F Method 509.4, Procedure 1	MIL810F Method 509.4, Procedure 1
Dust:	MIL810F Method 510.4, Procedure 1	MIL810F Method 510.4, Procedure 1	MIL810F Method 510.4, Procedure 1	MIL810F Method 510.4, Procedure 1	MIL810F Method 510.4, Procedure 1
Vibration:	MIL810F Method 514.5, Procedure 1, Category 24	MIL810F Method 514.5, Procedure 1, Category 24	MIL810F Method 514.5, Procedure 1, Category 24	MIL810F Method 514.5, Procedure 1, Category 24	MIL810F Method 514.5, Procedure 1, Category 24
Mechanical Shock:	MIL810F Method 516.5, Procedure 1	MIL810F Method 516.5, Procedure 1	MIL810F Method 516.5, Procedure 1	MIL810F Method 516.5, Procedure 1	MIL810F Method 516.5, Procedure 1
ESD:	IEC/EN61000-4-2	IEC/EN61000-4-2	IEC/EN61000-4-2	IEC/EN61000-4-2	IEC/EN61000-4-2
IP Rating*:	IP57	IP54	IP54	IP54	IP57

*IP54 – 4 stands for protection against water sprayed from all directions
IP57 – 7 stands for submersibility tested at 1 meter for 30 minutes

Magnum Electronics, Inc

927 Horsepond Road
Dover, DE 19901
302-734-9250
302-734-1056 Fax
main@magnumelectronics.com

www.magnumelectronics.com



MOTOROLA SOLUTIONS

Radio Solutions Channel Partner

MOTOROLA SOLUTIONS

PLATINUM CHANNEL PARTNER

Manufacturers Representative
Professional & Commercial Radio Elite Specialist
P25 Systems

All features, functionality and other product specifications are subject to change without notice or obligation. No warranty or guarantee expressed or implied is made regarding the capacity, performance or suitability of any product.

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their respective owners. © Motorola, Inc. 2008. All rights reserved.
02/08
MOTOTRBORSM